

## Routine Maintenance, Cleaning. Stella Interlocking tiles.

### Prevention

- Always protect floors when moving heavy objects to prevent permanent scratches and tears in the wear layer
- The use of appropriate wide floor protectors under tables, chairs and any heavy furnishing to avoid permanent damage.
- Place walk-off mats at all entrances, this helps protect the Interlocking Tiles from water, grease, sand and soil which all can cause un-repairable damage and can affect the aesthetic appearance of you flooring.
- During peak sunlight hours the use of blinds or curtains is highly recommended, prolonged direct sunlight can result in discoloration and volatile temperature variations causing damage to your floor.
- Do not allow solvents of any kind to penetrate between the interlocking tile as this can cause delamination of the tiles many layers.

### Routine Cleaning.

- Routine Cleaning is an important step towards the longevity of your Interlocking Tile in particular the removal of particles which in turn could abrade the surface of your tile.
- Daily sweeping and damp mopping is recommended , large amounts of water should be mopped up immediately, if more aggressive cleaning is required use a PH neutral cleaning product which must be sanctioned by a Stella Floorcoverings agent.
- All stain forming and aggressive substances must be removed immediately from the surface as this could cause permanent damage.
- Professional cleaning from a licensed cleaning company must be undertaken and recorded as per the Limited Warranty.