

## Technical Data Sheet



**STELLA**  
FLOOR COVERINGS

### BURLINGTON LVT

BURLINGTON LVT is made from 100% safe and environmentally friendly virgin material. BURLINGTON LVT is suitable for commercial use such as hospitals, offices, sports facilities, schools and supermarkets.



### SPECIFICATIONS:

Design	Burlington
Colours Available	Iron & Red Dog
Surface	Dual-PUR
Finish	Semi Gloss
Wear Layer	0.70mm
Total Thickness	3.0mm
Plank Size	457mm x 457mm
Installation	Glue Down
Commercial/Residential	Commercial
Indoor or Outdoor	Indoor
Tiles per Box	16
Box weight	18.5kg
Square Meterage Per Box	3.34m <sup>2</sup>
Classification (use area) EN10582	Commercial 33 (Heavy)
Wear Resistance EN 660-2	Group T
Fire Classification ISO 9239-1	
“- Critical Radiant Flux (CRF)	≥ 8.9kW/m <sup>2</sup>
“- Smoke Development Rate	≤ 243%. Minutes
Slip Resistance AS 4586 (Appendix A)	P3

NOTE: Colours may vary from Printed Colour Brochure.  
Specifications subject to normal manufacturing tolerances and may be changed without prior notice.

[www.stellafloorcoverings.com.au](http://www.stellafloorcoverings.com.au)

11 Belmont Avenue Belmont Perth Western Australia 6104  
M: +61 414 864 936 P: +61 8 9277 7177 F: +61 8 9277 6164

