Technical Data Sheet



INTERLOCK:

Stella Floorcoverings Interlock Tile is a high performing Luxury Vinyl Tile for use in heavy commercial application or when a temporary floor is required with minimal damage to the existing floorcoverings. These tiles have an intergrated locking system so no adhesive is required when installing.



SPECIFICATIONS:

Style Name	INTERLOCK
Colours Available	Liquorice Black
Tile Size	914mm x 914mm
Tile Thickness	5mm
Wearlayer Thickness	0.7mm
Weight	7590g/m ² per tile
Surface Treatment	Anti-Bacterial / Anti-Fungial
Abrasion Group	(EN 660-2) Class T
Slip Resistance	P3 / R10
Impact Sound Reduction	9db
Impact Sound Reduction VOC Emissions	9db Very Low VOC
•	
VOC Emissions	Very Low VOC
VOC Emissions Backing	Very Low VOC PVC
VOC Emissions Backing CHF Value	Very Low VOC PVC 7.7kW/m ²
VOC Emissions Backing CHF Value Resistance to chemicals	Very Low VOC PVC 7.7kW/m ² No defects
VOC Emissions Backing CHF Value Resistance to chemicals Tiles per box	Very Low VOC PVC 7.7kW/m ² No defects 3

NOTE: Colours may vary from Printed Colour Brochure. Specifications subject to normal manufacturing tolerances and may be changed without prior notice.

www.stellafloorcoverings.com.au

 11 Belmont Avenue Belmont Perth Western Australia 6104

 M: +61 414 864 936
 P: +61 8 9277 7177
 F: +61 8 9277 6164